

SUPER HIGH HEAT™

Product # 618

Heavy-duty granular drain opener

This drain opener contains extra powerful caustic granules activated with aluminum needles to quickly unclog drains and sewers and keep them free-flowing. When added to water, it releases large amounts of heat and turbulence to liquefy, dissolve and loosen fats, oils and other organic matter that typically clog drains and sewer lines. It offers the fastest action available in a non-acid drain opener.

Use in:

- Manholes
- Drains
- Food Plants
- Packing Houses
- Canneries

Effective Against

- Animal fats
- Hair
- Organic matter
- Vegetable oils
- Paper
- Hard-water soap deposits

Features and Benefits

- Contains extra caustic and heat generating aluminum needles.
- Releases tremendous amounts of heat and turbulence to liquefy blockages in drain and sewers for the fastest action available in a non-acid drain opener.

Properties

Appearance.....	Red pellets with aluminum granules
Fragrance.....	None
Flash point.....	None
pH.....	14.0
Stability.....	1 year
Solubility in water.....	Complete (very reactive)

Directions Complete directions on product label

Manholes: Pour or shovel 20 pounds into manholes above the clog.
Industrial: Use 1-2 pounds in normal drains. Where grease or organic waste is high, use 3-5 pounds.

Authorizations

NSF L1: Compounds for use in sewage or drain lines.

Ingredients

Sodium Hydroxide	
Sodium Nitrate	
Aluminum Metal	
Sodium Chloride	
Red Dye	

CAS Number

1310-73-2
7631-99-4
7429-90-5
7647-14-5
Mixture


Safety

DANGER: Harmful in contact with skin. Causes severe skin burns and eye damage.

DOT Shipping (ground transportation)

Proper Shipping Name:	Corrosive solid, basic, inorganic, n.o.s. (Sodium Hydroxide)
Class:	8
ID Number:	UN3262
Packing Group:	II

NFPA® RATINGS



Quantities

50 pound pail